

SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG | PRODUCT<br>PICTURE FOR<br>REFERENCE | DESCRIPTION | LIGHT<br>SOURCE | LED DRIVER<br>TYPE | MOUNTING | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA | PROJECT TYPE |                        |                      |
|-----|-------------------------------------|-------------|-----------------|--------------------|----------|----------------------------------|-----|------|--------------|------------------------|----------------------|
|     |                                     |             |                 |                    |          |                                  |     |      | NEW          | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |

GENERAL NOTES:



1. CPS designated light fixtures tags shall be used on all projects. Do not relabel light fixtures.
2. LED products shall be "Design Lights Consortium (DLC) Approved and Listed" or shall be Energy Star labeled.
3. Refer to the following link <http://www.designlights.org> for products qualification.
4. CPS preference is to use DLC listed light fixtures.
5. Downlights and decorative fixtures are not able to meet DLC listing currently.
6. Some manufacturers stay on the schedule for competitive BIDs despite lacking a DLC listing.
7. LED delivered lumens selection shall be confirmed with photometric calculations done by lighting designer/electrical engineer and comply with CPS and IES recommended light levels.
8. LED 0-10v dimmable drivers shall be utilized based on the control's strategy.
9. Provide specification grade products only.
10. Refer to Architectural Drawings for Ceiling types and construction.
11. Catalog numbers represent general series information only.
12. All fixtures to be fused.

| TAG | PRODUCT<br>PICTURE FOR<br>REFERENCE | DESCRIPTION | LIGHT<br>SOURCE | LED DRIVER<br>TYPE | MOUNTING | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA | PROJECT TYPE |                        |                      |
|-----|-------------------------------------|-------------|-----------------|--------------------|----------|----------------------------------|-----|------|--------------|------------------------|----------------------|
|     |                                     |             |                 |                    |          |                                  |     |      | NEW          | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |

|     |                                                                                     |                                                                               |                       |                     |                  |                         |    |                                                                     |   |   |  |
|-----|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------|---------------------|------------------|-------------------------|----|---------------------------------------------------------------------|---|---|--|
| LD1 |    | 4" aperture round LED downlight, comfort clear diffuse reflector              | LED 3500K 1000 lumens | Integral LED driver | Recessed, varies | LIGHTOLIER - C4R-C4RDL  | NO | Conference rooms, Lobby, Reception, Chicago Plenum Where Applicable | X | X |  |
|     |                                                                                     |                                                                               |                       |                     |                  | GOTHAM - IVO 4          | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PORTFOLIO - LD4D        | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PRESCOLITE – LTR-4RD    | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | HEW – 4DR               | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | LITELINE – GEN04        | NO |                                                                     |   |   |  |
| LD2 |  | 4" aperture round LED wall washer downlight, comfort clear diffuse reflector, | LED 3500K 1000 lumens | Integral LED driver | Recessed         | LIGHTOLIER - C4R-C4R WW | NO | Conference rooms, Lobby, Reception, Chicago Plenum Where Applicable | X | X |  |
|     |                                                                                     |                                                                               |                       |                     |                  | GOTHAM - IVO 4 WW       | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PORTFOLIO - LD4C WW     | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PRESCOLITE - LTR-4RD WW | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | HEW – 4DR WW            | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | LITELINE - GEN04 Z      | NO |                                                                     |   |   |  |
| LD3 |  | 4" aperture round LED downlight, wet rated, comfort clear diffuse reflector   | LED 3500K 1300 lumens | Integral LED driver | Recessed         | LIGHTOLIER - C4R-C4RDL  | NO | Restrooms, lockers, Chicago Plenum Where Applicable                 | X | X |  |
|     |                                                                                     |                                                                               |                       |                     |                  | GOTHAM - IVO 4          | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PORTFOLIO - LD4D        | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | PRESCOLITE – LTR-4RD    | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | HEW – 4DR               | NO |                                                                     |   |   |  |
|     |                                                                                     |                                                                               |                       |                     |                  | LITELINE – GEN04        | NO |                                                                     |   |   |  |

SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG | PRODUCT PICTURE FOR REFERENCE                                                       | DESCRIPTION                                                                                                                 | LIGHT SOURCE                                           | LED DRIVER TYPE     | MOUNTING                                             | MANUFACTURER – CATALOG SERIES | DLC | AREA                                                                                                                                                                 | PROJECT TYPE |                     |                   |
|-----|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------|------------------------------------------------------|-------------------------------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------------|-------------------|
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      |                               |     |                                                                                                                                                                      | NEW          | EXISTING RENOVATION | EXISTING RETROFIT |
| LD4 |    | 4" aperture round LED downlight, shower wet rated, comfort clear diffuse reflector, nonconductive trim                      | LED 3500K 1300 lumens                                  | Integral LED driver | Recessed                                             | LIGHTOLIER - C4R-C4RDL-SL     | NO  | Showers, Chicago Plenum Where Applicable                                                                                                                             | X            | X                   |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LITHONIA - EVO 4 SHOWER       | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | PORTFOLIO - LD4C SHOWER       | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | PRESCOLITE – LTR-4RD-SH       | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | HEW – 4DR-S                   | NO  |                                                                                                                                                                      |              |                     |                   |
| LI1 |    | 4' LED Enclosed & Gasketed, fiberglass housing Industrial strip                                                             | LED 3500K 5500 lumens                                  | Integral LED driver | Surface or Pendant                                   | METALUX – VT2 LED             | YES | Boiler Room, Electrical Room, Mechanical Room<br>Option for low ceilings. Kitchen, Auxiliary pool areas, lockers rooms Damp/Wet Location                             | X            | X                   | X                 |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | COLUMBIA - LXEM               | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LITHONIA – FEM                | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | DAYBRITE – V3WLED             | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | HEW - 96 LED                  | NO  |                                                                                                                                                                      |              |                     |                   |
| LL1 |    | 4" aperture LED linear recessed continuous slots                                                                            | LED 3500K 500 lumens/per FT                            | Integral LED driver | Recessed                                             | LEDALITE – TRUGROOVE          | YES | Conference rooms, Lobby, Reception Chicago Plenum Where Applicable                                                                                                   | X            |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LUMENWERX – VIA 4LED          | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | AXIS- BEAM4 BBRLED            | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | FOCAL POINT- SEEM 4           | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | PRU – BRPO4-REC               | YES |                                                                                                                                                                      |              |                     |                   |
| LP1 |   | Suspended 4FT or 8FT LED linear direct/indirect with frosted bottom lens and top dust cover, individual or continuous mount | LED 3500K 4600 lumens/ per 4 FT                        | Integral LED driver | Rigid stem or Aircraft cable Pendant per application | FINELITE - SERIES 16 LED      | NO  | Classrooms, Offices Option for high ceilings                                                                                                                         | X            |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | CORELITE – JAYLUM J3          | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | MARK ARCH - PLANAR            | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | AXIS – SLIM                   | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LEDALITE - SYNCLINE           | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LITECONTROL-STANCE            | YES |                                                                                                                                                                      |              |                     |                   |
| LP2 |  | 8" to 16" wide 4FT LED Lensed Wraparound                                                                                    | LED 3500K 4600 lumens                                  | Integral LED driver | Rigid stem Pendant                                   | DAY-BRITE – OWL               | YES | Classrooms                                                                                                                                                           |              | X                   | X                 |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | LITHONIA –SBL4                | YES |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | HEW – 18 LED                  | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | COLUMBIA LAW                  | YES |                                                                                                                                                                      |              |                     |                   |
| LP3 |  | Asymmetric throw Indirect uplight luminaire with tempered glass lens, Wet and Natatorium rated application                  | LED 3500K Lumens TBD based on photometric calculations | Integral LED driver | Pendant or wall mount                                | METRIX – ASYX 2.0             | YES | Indoor Swimming Pool Aim optic forward to illuminate the ceiling. UL Wet Location and Natatorium rated, Provide photometric evaluation based on the mounting heights | X            | X                   |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | ALIGHT – ANG4                 | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | SPI - ECHO                    | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      | ELLIPTIPAR – S126 VP          | NO  |                                                                                                                                                                      |              |                     |                   |
|     |                                                                                     |                                                                                                                             |                                                        |                     |                                                      |                               |     |                                                                                                                                                                      |              |                     |                   |

NAME OF SCHOOL  
PROJECT NUMBER

26 51 00.01 - 2

INTERIOR LIGHTING FIXTURE SCHEDULE  
INCLUDE ON DRAWINGS, EDIT PER PROJECT

SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG  | PRODUCT<br>PICTURE FOR<br>REFERENCE                                                 | DESCRIPTION                                                                                                                            | LIGHT<br>SOURCE                                           | LED DRIVER<br>TYPE  | MOUNTING           | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA                                                                                                                                                      | PROJECT TYPE |                        |                      |
|------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------|--------------------|----------------------------------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|------------------------|----------------------|
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    |                                  |     |                                                                                                                                                           | NEW          | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |
| LP4  |    | 16" diameter Lensed LED low bay pendant with polycarbonate prismatic refractor, lensed on bottom, Wet and Natatorium rated application | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | KENALL - EPLB22                  | NO  | Gymnasium, Indoor Swimming Pool Bleachers areas, Deck, UL Wet Location and Natatorium rated, Provide photometric evaluation based on the mounting heights | X            | X                      |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | METEOR – DEXF-12                 | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    |                                  |     |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    |                                  |     |                                                                                                                                                           |              |                        |                      |
| LP5A |    | 24" diameter, 4" aperture LED lensed decorative RING luminaire, DIRECT/INDIRECT OR DIRECT DISTRIBUTIONS                                | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG – O-20            | NO  | Library, Communities spaces                                                                                                                               | X            |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LIGHTNET -RINGO-STAR P1          | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | IMPACT – ULA LED                 | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LUMENWERX-CURVIA 4               | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | FINELITE-HP4 CIRCLE              | NO  |                                                                                                                                                           |              |                        |                      |
| LP5B |    | 36" diameter, 4" aperture LED lensed decorative RING luminaire, DIRECT/INDIRECT OR DIRECT DISTRIBUTIONS                                | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG– O-30             | NO  | Library, Communities spaces                                                                                                                               | X            |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LIGHTNET-RINGO-STAR P1           | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | IMPACT – ULA LED                 | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LUMENWERX-CURVIA 4               | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | FINELITE-HP4 CIRCLE              | NO  |                                                                                                                                                           |              |                        |                      |
| LP5C |  | 48" diameter, 4" aperture LED lensed decorative RING luminaire, DIRECT/INDIRECT OR DIRECT DISTRIBUTIONS                                | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG – O-40            | NO  | Library, Communities spaces                                                                                                                               | X            |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LIGHTNET-RINGO-STAR P1           | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | IMPACT – ULA LED                 | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LUMENWERX-CURVIA 4               | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | FINELITE-HP4 CIRCLE              | NO  |                                                                                                                                                           |              |                        |                      |
| LP6A |  | 24" diameter LED lensed decorative DRUM luminaire                                                                                      | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG – P3920           | NO  | Library, Communities spaces                                                                                                                               | X            |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | PINNACLE – FINA F24D             | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | NAL – EC-BEN                     | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | FOCAL POINT – FSDL22             | NO  |                                                                                                                                                           |              |                        |                      |
|      |                                                                                     |                                                                                                                                        |                                                           |                     |                    | LUMENWERX- POP CORE              | NO  |                                                                                                                                                           |              |                        |                      |


SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG  | PRODUCT<br>PICTURE FOR<br>REFERENCE                                                 | DESCRIPTION                                                      | LIGHT<br>SOURCE                                                    | LED DRIVER<br>TYPE  | MOUNTING           | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA                        | PROJECT TYPE |                        |                      |
|------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|--------------------------------------------------------------------|---------------------|--------------------|----------------------------------|-----|-----------------------------|--------------|------------------------|----------------------|
|      |                                                                                     |                                                                  |                                                                    |                     |                    |                                  |     |                             | NEW          | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |
| LP6B |    | 36" diameter LED lensed decorative DRUM luminaire                | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG – P3930           | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | PINNACLE – FINA F36D             | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | NAL – EC-BEN                     | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | FOCAL POINT – FSDL33             | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | LUMENWERX- POP CORE              | NO  |                             |              |                        |                      |
| LP6C |    | 48" diameter LED lensed decorative DRUM luminaire                | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG – P3940           | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | PINNACLE – FINA F48D             | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | NAL – EC-BEN                     | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | FOCAL POINT – FSDL44             | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | LUMENWERX- POP CORE              | NO  |                             |              |                        |                      |
| LP7A |    | 24" x 24" LED lensed decorative SQUARE luminaire                 | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG- P3624            | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | PINNACLE – LIFT LF22D            | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | NAL – ATMOS                      | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | LUMENWERX- POP CORE              | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | BETA CALCO-TIMPANI SQ            | NO  |                             |              |                        |                      |
| LP7B |   | 36" x 36" LED lensed decorative SQUARE luminaire                 | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG- P3633            | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | NAL – ATMOS                      | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | BETA CALCO-TIMPANI SQ            | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    |                                  |     |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    |                                  |     |                             |              |                        |                      |
| LP7C |  | 48" x 48" LED lensed decorative SQUARE luminaire                 | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG- P3644            | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | PINNACLE – LIFT LF44D            | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | NAL – ATMOS                      | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | LUMENWERX- POP CORE              | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | BETA CALCO-TIMPANI SQ            | NO  |                             |              |                        |                      |
| LP8A |  | 24" x 24" with 4" aperture LED lensed decorative FRAME luminaire | LED 3500K<br>Lumens TBD<br>based on<br>photometric<br>calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG-BPRO4-SQ-LIN      | NO  | Library, Communities spaces | X            |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | PINNACLE – QIVI-Q3S              | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | AXIS-BEAM 4                      | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | LUMENWERX- VIA 4 PATTERNS        | NO  |                             |              |                        |                      |
|      |                                                                                     |                                                                  |                                                                    |                     |                    | FOCAL POINT SEEM4                |     |                             |              |                        |                      |

SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG  | PRODUCT<br>PICTURE FOR<br>REFERENCE                                                 | DESCRIPTION                                                                     | LIGHT<br>SOURCE                                           | LED DRIVER<br>TYPE  | MOUNTING           | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA                                                                                                                                | PROJECT TYPE        |                        |                      |
|------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------|--------------------|----------------------------------|-----|-------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------|----------------------|
|      |                                                                                     |                                                                                 |                                                           |                     |                    |                                  |     |                                                                                                                                     | NEW                 | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |
| LP8B |    | 36" x 36" with 4" aperture LED lensed decorative FRAME luminaire                | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG-BPRO4-SQ-LIN      | NO  | Library, Communities spaces                                                                                                         | X                   |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | PINNACLE – QIVI-Q3S              | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | AXIS-BEAM 4                      | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | LUMENWERX- VIA 4 PATTERNS        | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | FOCAL POINT SEEM4                |     |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    |                                  |     |                                                                                                                                     |                     |                        |                      |
| LP8C |    | 48" x 48" with 4" aperture LED lensed decorative FRAME luminaire                | LED 3500K<br>Lumens TBD based on photometric calculations | Integral LED driver | Surface or pendant | PRUDENTIAL LTG-BPRO4-SQ-LIN      | NO  | Library, Communities spaces                                                                                                         | X                   |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | PINNACLE – QIVI-Q3S              | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | AXIS-BEAM 4                      | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | LUMENWERX- VIA 4 PATTERNS        | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | FOCAL POINT SEEM4                |     |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    |                                  |     |                                                                                                                                     |                     |                        |                      |
| LR1  |   | 6" aperture perimeter LED luminaire with distribution asymmetrical to the space | LED 3500K<br>500-800 lumens per FT                        | Integral LED driver | Recessed           | PRUDENTIAL LTG-BPRO5-PER         | YES | Restrooms, lockers<br>Chicago Plenum<br>Where Applicable                                                                            | X                   |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | LUMENWERX – VIA5 PER             | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | LITECONTROL 6L-WS-D              | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | AXIS-BEAM 6                      | NO  |                                                                                                                                     |                     |                        |                      |
| LS1  |  | 4FT Narrow LED Lensed Wraparound, <10" wide, vandal proof                       | LED 3500K<br>4600 lumens                                  | Integral LED driver | Surface            | KENALL-MLHA8 LED                 | NO  | Corridors, Stairways                                                                                                                | X<br>Stairways only | X                      | X                    |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | FAIL-SAFE- HVL8 LED              | YES |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | PARAMOUNT- VRSW7                 | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | CURRENT LIFESHIELD PVNT          | NO  |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | NEW STAR – VIC 4W                | YES |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    |                                  |     |                                                                                                                                     |                     |                        |                      |
| LS2  |  | LED Low Bay Industrial (LINEAR PROFILE)                                         | LED 3500K<br>Lumens TBD based on photometric calc         | Integral LED driver | Surface            | LITHONIA -XIB                    | YES | Boiler Room, Electrical Room, Mechanical Room, with higher ceilings<br>Provide photometric evaluation based on the mounting heights | X                   | X                      | X                    |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | HEW-GS LED                       | YES |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    | ILP-ENDEAVOUR                    | YES |                                                                                                                                     |                     |                        |                      |
|      |                                                                                     |                                                                                 |                                                           |                     |                    |                                  |     |                                                                                                                                     |                     |                        |                      |



SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG | PRODUCT PICTURE FOR REFERENCE                                                       | DESCRIPTION                                                          | LIGHT SOURCE                                   | LED DRIVER TYPE     | MOUNTING           | MANUFACTURER – CATALOG SERIES | DLC | AREA                                                                                                     | PROJECT TYPE |                     |                   |
|-----|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|------------------------------------------------|---------------------|--------------------|-------------------------------|-----|----------------------------------------------------------------------------------------------------------|--------------|---------------------|-------------------|
|     |                                                                                     |                                                                      |                                                |                     |                    |                               |     |                                                                                                          | NEW          | EXISTING RENOVATION | EXISTING RETROFIT |
| LS3 |    | LED High Bay luminaire with frosted acrylic lens, wire guard         | LED 3500K Lumens TBD based on photometric calc | Integral LED driver | Surface or pendant | DAY-BRITE - FBY               | YES | Gymnasium<br><br>Provide photometric evaluation based on the mounting heights                            | X            | X                   | X                 |
|     |                                                                                     |                                                                      |                                                |                     |                    | LITHONIA - IBG                | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | COLUMBIA – LLHV               | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | METALUX – OHB                 | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | HEW – GH LED                  | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | ILP-ENDEAVOUR                 | YES |                                                                                                          |              |                     |                   |
| LT1 |    | 2'x4' LED ambient lensed troffer, regressed aluminum door            | LED 3500K 4600 lumens                          | Integral LED driver | Recessed           | LITHONIA – 2GTL LED           | YES | Lunchrooms, Corridors,<br><br>Chicago Plenum Where Applicable                                            | X            | X                   |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | METALUX-24GR LED              | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | HEW – 50 LED                  | NO  |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | CURRENT-LBRB 24               | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    |                               |     |                                                                                                          |              |                     |                   |
| LT2 |    | 2'x4' LED troffer with acrylic basket                                | LED 3500K 4600 lumens                          | Integral LED driver | Recessed           | LITHONIA – 2BLT4              | YES | Classrooms, Offices, Lunchrooms, Corridors.<br>Chicago Plenum Where Applicable                           | X            | X                   |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | METALUX – 24CZ                | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | COLUMBIA - LCAT24             | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | FOCAL POINT - FAM2            | NO  |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | DAY-BRITE – FLUXGRID          | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | HEW – PT LED                  | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | CURRENT-LVT 24                | YES |                                                                                                          |              |                     |                   |
| LT3 |  | 2'x4' LED volumetric troffer with opal diffuser door                 | LED 3500K 4600 lumens                          | Integral LED driver | Recessed           | FINELITE - HPR-24 DCO-LED     | NO  | Classrooms, Offices, Lunchrooms, Corridors, Library, Community space.<br>Chicago Plenum Where Applicable | X            | X                   |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | MARK LIGHTING - WHSPR         | NO  |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | LEDALITE-SHINE                | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | LITECONTROL-RYVL 55L          | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    |                               |     |                                                                                                          |              |                     |                   |
| LT4 |  | 2'x4' LED volumetric troffer with opal diffuser door surface mounted | LED 3500K 4600 lumens                          | Integral LED driver | Surface            | FINELITE - HPR-24 DCO-LED SM  | NO  | Classrooms, Offices, Lunchrooms, Corridors, Library                                                      | X            | X                   |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | MARK LIGHTING – WHSPR SMK     | NO  |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | LEDALITE-SHINE                | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    | LITECONTROL-RYVL 55L          | YES |                                                                                                          |              |                     |                   |
|     |                                                                                     |                                                                      |                                                |                     |                    |                               |     |                                                                                                          |              |                     |                   |

SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG      | PRODUCT<br>PICTURE FOR<br>REFERENCE                                                 | DESCRIPTION                                                                           | LIGHT<br>SOURCE                  | LED DRIVER<br>TYPE     | MOUNTING                            | MANUFACTURER –<br>CATALOG SERIES | DLC | AREA                                                                                                              | PROJECT TYPE |                        |                      |
|----------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------|------------------------|-------------------------------------|----------------------------------|-----|-------------------------------------------------------------------------------------------------------------------|--------------|------------------------|----------------------|
|          |                                                                                     |                                                                                       |                                  |                        |                                     |                                  |     |                                                                                                                   | NEW          | EXISTING<br>RENOVATION | EXISTING<br>RETROFIT |
| LT5      |    | 1'x4' LED ambient<br>Lensed troffer<br>regressed aluminum<br>door                     | LED<br>3500K<br>4300 lumens      | Integral<br>LED driver | Recessed                            | LITHONIA – GTL LED               | YES | Restrooms, Corridors,<br>Stairways<br><br>Chicago Plenum<br>Where Applicable                                      | X            | X                      |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | METALUX - GR LED                 | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | COLUMBIA-LJT14                   | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | HEW – 50 LED                     | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | CURRENT-LBRB 14                  | YES |                                                                                                                   |              |                        |                      |
| LT6      |    | 1'x4' LED Lensed<br>Troffer, surface mount                                            | LED<br>3500K<br>4300 lumens      | Integral<br>LED driver | Surface or<br>Rigid stem<br>Pendant | LITHONIA-GTL                     | YES | Restrooms, Corridors,<br>Stairways                                                                                | X            | X                      |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | METALUX – GR SK14 LED            | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | COLUMBIA-LJT14-SM                | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | HEW – 11 LED                     | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | CURRENT LBRB 14                  | YES |                                                                                                                   |              |                        |                      |
| LT7      |    | 4' diameter LED round<br>skydome with flat acrylic<br>lens                            | LED<br>3500K<br>10,000<br>lumens | Integral<br>LED driver | Recessed                            | FOCAL POINT - FSDL               | NO  | Lobby, Lunchrooms,<br>Corridors.<br><br>Chicago Plenum<br>Where Applicable                                        | X            |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | PRUDENTIAL - 9000                | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | MARK- MGL                        | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | LUMENWERX – POP                  | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | HEW - RND                        | NO  |                                                                                                                   |              |                        |                      |
| LT8      |   | 1'x4' LED lensed troffer<br>vandal proof                                              | LED<br>3500K<br>4300 lumens      | Integral<br>LED driver | Recessed                            | FAILSAFE- GRV LED (not<br>CP)    | NO  | Restrooms, lockers<br><br>Provide fixtures with<br>Chicago Plenum (CP)<br>rating if Applicable<br>UL Wet Location | X            | X                      |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | LITHONIA – VRTL (not CP)         | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | HEW – V50                        | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | PARAMOUNT-G1 (not CP)            | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | KURTZON-VL-R-LED                 | YES |                                                                                                                   |              |                        |                      |
| LW1      |  | 4FT LED Wall mount<br>linear indirect, up to 9"<br>protrusion from wall               | LED<br>3500K<br>4600 lumens      | Integral<br>LED driver | Wall mount                          | FINELITE - Series 18 WALL<br>LED | NO  | Classrooms, Offices<br>Option for high ceilings                                                                   | X            |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | CORELITE - JAYLUM JW             | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | LEDALITE – SYNC WALL<br>LED      | NO  |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | LITECONTROL-STANCE<br>WALL       | YES |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | MARK ARCH LTG- PLANAR            | NO  |                                                                                                                   |              |                        |                      |
| LW1<br>A |  | 4FT LED Wall mount<br>linear indirect,<br>ADA compliant- <4"<br>protrusion from wall) | LED<br>3500K<br>4600 lumens      | Integral<br>LED driver | Wall mount                          | FINELITE - Series 18 WALL<br>LED | NO  | Classrooms, Offices<br>Option for high ceilings                                                                   | X            |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     | CORELITE - JAYLUM JW             |     |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     |                                  |     |                                                                                                                   |              |                        |                      |
|          |                                                                                     |                                                                                       |                                  |                        |                                     |                                  |     |                                                                                                                   |              |                        |                      |

NAME OF SCHOOL  
PROJECT NUMBER

26 51 00.01 - 7

INTERIOR LIGHTING FIXTURE SCHEDULE  
INCLUDE ON DRAWINGS, EDIT PER PROJECT



SECTION 26 51 00.01  
INTERIOR LIGHTING FIXTURE SCHEDULE

~~~ PROJECT NOTE ~~~~~  
LIGHT FIXTURE SCHEDULE INTENDED FOR USE ON DRAWINGS, NOT IN PROJECT MANUAL,  
EOR (ENGINEER OF RECORD) TO EDIT TO REFLECT PROJECT SCOPE  
~~~ END OF PROJECT NOTE ~~~~~

| TAG | PRODUCT PICTURE FOR REFERENCE                                                      | DESCRIPTION                                                                                                                            | LIGHT SOURCE          | LED DRIVER TYPE     | MOUNTING                                    | MANUFACTURER – CATALOG SERIES | DLC | AREA                                                                                                                                                                     | PROJECT TYPE |                     |                   |
|-----|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|-----------------------|---------------------|---------------------------------------------|-------------------------------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------------|-------------------|
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             |                               |     |                                                                                                                                                                          | NEW          | EXISTING RENOVATION | EXISTING RETROFIT |
| LW2 |   | 4FT LED round omni-directional lensed Wall Mount                                                                                       | LED 3500K 4100 lumens | Integral LED driver | Wall mount                                  | LITHONIA- CLX                 | YES | Stairways                                                                                                                                                                | X            | X                   |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | METALUX - SNLED               | YES |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | DAY-BRITE –FSS                | YES |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | HEW – 75 LED                  | YES |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | COLUMBIA - MPS                |     |                                                                                                                                                                          |              |                     |                   |
| X1  |   | Edge-lit LED Specification-grade Exit Sign (AC or DC) Chicago Approved.                                                                | LED                   | Integral LED driver | Recessed/ Surface/ Ceiling/ or Wall-mounted | CHLORIDE – CE                 | n/a | Mounting as necessary for application. For exits with EM batteries, provide with self-diagnostic-PREFERABLE                                                              | X            | X                   | X                 |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | SURE-LITES - ECHX             | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | LITHONIA - EDGC               | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | HEW – EXIT/EL/CHICAGO         | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | ISOLITE - PG2                 | n/a |                                                                                                                                                                          |              |                     |                   |
| X2  |   | LED Specification-grade Steel Exit Sign (AC or DC) Chicago Approved.                                                                   | LED                   | Integral LED driver | Surface/Ceiling/ or Wall-mounted            | CHLORIDE – CSE                | n/a | Mounting as necessary for application. Provide wire guard and stem kit as required for application. For exits with EM batteries, provide with self-diagnostic-PREFERABLE | X            | X                   | X                 |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | SURE-LITES - CHX              | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | LITHONIA – LXC                | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | HEW – EXIT/CHICAGO            | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | ISOLITE - CLP                 | n/a |                                                                                                                                                                          |              |                     |                   |
| EBU |  | LED Battery Pack Unit with Attached Heads, nickel cadmium battery or nickel metal hydride battery. 90-minute battery, Chicago Approved | LED                   | Integral LED driver | Surface                                     | SURE-LITES - SELM60R4SD       | n/a | Provide with self-diagnostic-PREFERABLE                                                                                                                                  | X            | X                   | X                 |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | CHLORIDE – CSU                | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             | LITHONIA – TCU                | n/a |                                                                                                                                                                          |              |                     |                   |
|     |                                                                                    |                                                                                                                                        |                       |                     |                                             |                               |     |                                                                                                                                                                          |              |                     |                   |