

- NOTES:
  1. PROWIDE A 24"W x 24"L x12"D NEMA 4X RATED ENCLOSURE WITH LOCKING DOOR.
  2. THE ENCLOSURE'S DOOR SHALL BE MONITORED BY DOOR POSITION SWITCH CONNECTED TO THE EXISTING HONEYWELL WISTA 50P INTRUSION DETECTION SYSTEM.
  3. EACH COMPONENT SHALL BE MOUNTED WITH A MINIMUM OF 2" OF SPACE BETWEEN ADJACENT COMPONENTS OR THE ENCLOSURE WALL.
  4. REFER TO SITE PLAN AND DETAILS FOR CABLE REQUIREMENTS AND ROUTING.
  5. PROVIDE A 8AWG GROUNDING CABLE CONNECTION TO SEMPLIENT GROUND IN IT ENCLOSURE, POWER RECEPTACLE.
  6. PROVIDE PLUGS TO ENSURE WATER DOES NOT SEEP INTO THE ENCLOSURE.

CHICAGO PUBLIC SCHOOLS CAPITAL IMPROVEMENT PROGRAM OFFICE OF SAFETY AND SECURITY

SECURITY STANDARDS

IT ENCLOSURE "NE-1"DETAIL WIRELESS BRIDGE FOR CAMERA ONLY POLES

